

Table 2 . Post-Remediation PCB Results
Monitoring Well 6I
Bennett's Dump, Bloomington, Indiana

Sample ID	Sampling Date	PCB ^a , ppb	Data Validated?	TSS, mg/L	Conductivity, uS/cm	Temperature, °C	Flow, gal/min	pH, S.U.	Turbidity, ntu
BD9258	05-Mar-02	0.28	Y	2	558	10.9	NA	NA	0.91
BD9259(DUP)	05-Mar-02	0.36	Y	< 1	558	10.9	NA	NA	0.91
BD9233	07-Dec-01	2.8	Y	< 1	667	13.7	NA	NA	1.5
BD9219	18-Sep-01	0.65	Y	< 1	608	21.6	NA	NA	0.71
BD9212	12-Jun-01	0.42	Y	52	530	14.6	NA	7.1	NA
BD9072	23-Feb-01	1.2	Y	NA	485	9.6	NA	6.3	NA
BD9058	03-Oct-00	0.17 J	Y	5	650	16.8	NA	7.0	NA
BD9048	23-Jun-00	0.29	Y	10	658	16.5	NA	7.0	NA
BD9029 ^b	30-Mar-00	< 0.1 J	Y	8	589	12.2	NA	6.8	NA
BD9018	28-Jan-00	< 0.1	Y	< 1	576	10.6	NA	7.2	NA
BD9009	11-Nov-99	0.13	Y	16	575	14.7	NA	7.1	NA

^a Samples were analyzed to a detection limit of 0.1 parts per billion (ppb) for all PCB parameters except Aroclor 1221 (detection limit 0.2 ppb or 0.5 ppb). Other detection limits may occasionally result from non-normal sample volumes, dilutions, etc.

^b Sample analyzed by Antech lab.

NR = Not reported.

J = Estimated value. The QA/QC data indicated an analytical bias.